# Xcellent<sub>®</sub> 12-350



13 Gauge

C

New upgraded - better grip, more lighter, smooth and comfortable. 13 gauge, cut level C, special XTech PU.

#### **KEY FEATURES**

- Cut protection level C with great abrasion resistance
- Special Xcellent XTech PU formulation contributes to better grip performance and extra softness and comfort
- New Upgraded lining with high quality yarns offers extra comfort, softness and lighter weight, smooth feeling
- Ergonomic, good fitting and flexible

# PRODUCT DETAILS

4543

CAT. II

i

Liner	UHMWPE mixed with other yarns
Gauge	13
Coating	Polyurethane
Finishing	Special XTech
Colour	Grey / Grey
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

4X43C

# **RECOMMENDED APPLICATIONS**

General purpose, or works with high cut hazard in dry conditions.

Such as handling sharp or rough edge materials, metal sheet, assembly, construction, repair, packaging, automotive industry...







# CERTIFICATION

Category II EN388:2016 Mechanical protection: levels obtained in laboratory tests Abrasion (min.0 to max. 4): Blade cut - coupe test (Index) (min.0 to Max. 5): Tear (min.0 to max. 4): Puncture (min.0 to max. 4): Cut resistance from sharp objects EN ISO 13997:1999 (min. A to Max. F, X - not tested): Impact protection (P if pass, F if failed):



EN420:2003+A1:2009 Dexterity (min.0 to max.5): level 5.

#### STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-350 can normally be 5 years.

#### CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

#### WARNNING

Don't use in case of chemicals, moving machines or electrical risk. Please ensure the products are strictly used within their protection levels.



