



Super flexible, great dexterity and comfortable. Special knitting. OEKO-TEX Standard 100. 13 gauge, nitrile.

KEY FEATURES

- Super flexible, great dexterity, soft and comfort
- OEKO-TEX standard 100 certified for skin friendly
- High quality coating makes it more durable
- 360° breathability to keep your hands cool
- Great fitting



PRODUCT DETAILS

Liner	Nylon mixed with other yarns
Gauge	13
Coating	Nitrile
Finishing	Foam
Colour	White / Grey
Size	6,7,8,9,10,11,12
Packing	2 pairs/pack, 12 pairs/polybag, 120 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose works under dry, little wet or little oily working conditions.

Such as general handling, assembly or disassembly works, inspection, precision works, logistics, sorting, warehousing, machine operating and etc.



CERTIFICATION


CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to Max. 5):	1
Tear (min.0 to max. 4):	2
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. 0 to Max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



4121X

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3008 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

